tesa® 55576

Product Information



1200 µm / 47.3 mils double sided PE foam tape

Product Description

tesa® 55576 is a double-sided PE foam tape for light duty mounting applications. It consists of a PE foam backing and a tackified acrylic adhesive.

Application Fields

- Trims & Profiles Mounting
- POS Signs & Advertising Material Mounting
- Mirror Pre-Mounting
- Temporary Mounting
- Gap Filling

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	PE foam	• Total thickness	1200 µm 47.2 mils
• Type of adhesive	acrylic		
• Type of liner	PE	• Color	white

Properties/Performance Values

• Temperature resistance long term	60 °C 140 °F	• Temperature resistance short term	80 °C 176 °F

Adhesion to Values

• Aluminium (initial)	6.4 N/cm 58.5 oz/in	• PVC (initial)	3 N/cm 27.4 oz/in
• PE (initial)	1.4 N/cm 12.8 oz/in	• Steel (initial)	5.5 N/cm 50.2 oz/in

For latest information on this product please visit http://l.tesa.com/?ip=55576

tesa® 55576

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit http://l.tesa.com/?ip=55576