




# tesa® 60412

## 70% PCR PET CST



### Product Information

#### Recycled PET Packaging Tape

#### Product Description

tesa® 60412 is a general-purpose packaging tape based on a 70% Post-Consumer Recycled (PCR) PET backing and a water-based acrylic adhesive system. tesa® 60412 has a strong and abrasion resistant backing with excellent bearing and wear properties. It features a very consistent, pressure sensitive acrylic adhesive, making this product the perfect solution for light- and medium-weight packaging application (max. 30 kg / 66 lbs). The material combination guarantees a quiet unwind and an excellent printability with all types of ink systems.

- The backing material is made of post-consumer recycled PET (70% recycled content).
- This product can be disposed together with the box into the blue bin without endangering the cardboard recycling process (certified according to INGEDE method 12).
- The production process of this product is solvent-free.

tesa® 60412 not only provides an outstanding performance, but it is also an advanced alternative contributing to sustainability: It also has a very good performance on recycled cardboards.

#### Sustainable Aspects

- Backing made with 70% recycled PET from post consumer waste
- Solvent-free production process
- Recycling friendly adhesive does not disturb the paper recycling process



For more information: <https://www.tesa.com/product-sustainability>

#### Product Features

- Backing made with 70% recycled post consumer waste
- Strong, tear and puncture resistant PET backing
- Versatile water based acrylic adhesive
- Smooth, silent unwinding
- Available in brown, white and transparent

#### Application Fields

- Sealing of cardboard boxes
- Suitable for light- and medium-weight packaging applications (max. 30 kg / 66 lbs)
- Excellent adhesion in recycled cardboards
- Suitable for manual and automatic dispensers
- Brand showcase and advertising purposes



# tesa® 60412

## 70% PCR PET CST

### Product Information

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

• Backing	PET	• Type of adhesive	water-based acrylic
• Bio-based carbon content of liner (acc. DIN EN 16640)	90 %	• Total thickness	56 µm 2.2 mils

### Product Assortment

• Available colors	white, brown, transparent
--------------------	------------------------------

### Properties/Performance Values

• Elongation at break	130 %	• Packaging Weight	Up to 30 kg
• Tensile strength	60 N/cm 34.3 lbs/in	• Silent unwinding	yes
• Automatic application	no	• Suitable for deep freezing	yes
• Hand tearability	low	• Transport Information	Temperature 0-70°C
• Humidity resistance	yes		

### Adhesion to Values

• Steel	3 N/cm 27.4 oz/in
---------	----------------------

### Certificates

#### Sustainability Certificates

- Tested according to INGEDE method 12. Test report available



# tesa® 60412

## 70% PCR PET CST

### Product Information

### Additional Information

Available in transparent. Chamois and white are available upon request.

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60412>