

# tesa® 64294 PV00

# Product Information



Low temperature compatible tensilised non-staining strapping tape

# **Product Description**

tesa® 64294 is a tensilised polypropylene strapping tape with a special natural rubber adhesive system.

tesa® 64294 features excellent low temperature compatibility. It provides a secure bond to various surfaces and can be removed without adhesive residue or delamination at low temperatures down to -10°C.

tesa® 64294 is specially designed for safe fixation of goods during all types of transports.

### **Product Features**

- tesa® 64294PV0 offers excellent low temperature compatibility
- It provides a secure bond to various surfaces and can be removed without adhesive residue or delamination at low temperatures down to -10°C.

# **Application Fields**

Closing, holding, securing and surface protection for all kinds of industries. For example, the appliance, office automation, furniture and metal industries.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

•	Backing	TPP	•	Total thickness	107 μm
•	Type of adhesive	natural rubber			4.2 mils
				Color	hlue

## **Properties/Performance Values**

•	Elongation at break	30 %	•	No discoloration	yes
•	Tensile strength	240 N/cm	•	Residue-free removability	yes
		137 lhs/in			

#### Adhesion to Values

•	Steel	2.6 N/cm
		23.8 oz/in



# tesa® 64294 PV00

**Product Information** 

# Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

