



tesa® 50120

Product Information



General purpose masking tape

Product Description

tesa® 50120 is a cost-efficient, creped paper masking tape, good for general-purpose bundling, holding, sealing, and surface protection applications. It provides excellent adhesion to a variety of surfaces.

Application Fields

- Light-duty bundling
- Packaging and closing
- Light-duty masking
- Paint masking

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------------------|---------------------|----------|
| • Backing | slightly-creped paper | • Thickness of tape | 123 µm |
| • Type of adhesive | synthetic rubber | | 4.8 mils |

Properties/Performance Values

- | | | | |
|-----------------------|----------------------|-------------------------------|-------|
| • Elongation at break | 12 % | • Temperature resistance min. | 16 °C |
| • Tensile strength | 35 N/cm
20 lbs/in | | 61 °F |

Adhesion to Values

- | | |
|---------|-----------------------|
| • Steel | 2.74 N/cm
25 oz/in |
|---------|-----------------------|



tesa[®] 50120

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=50120>