



tesa[®] 53030

Product Information

Spoolwound TPP for Bag Sequencing

Product Description

tesa[®] 53030 is a high-strength, tensilized polypropylene strapping tape with a specially formulated natural rubber adhesive system.

The natural rubber adhesive is cross-linked to provide residue-free removal as well as resistance to heat and cold. The adhesive formulation secures the bond throughout the entire process, at a variety of speeds, yet still removes cleanly from the surface.

We also offer tesa[®] 53030 in a variety of dimensions with outside diameter capabilities up to 14.5”.

Available Colors: Yellow

Application Fields

- Specific application is sequencing of bags on hand-pull equipment in the food processing industry

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|-----------|
| • Backing | TPP | • Total thickness | 116.84 µm |
| • Type of adhesive | natural rubber | | 4.6 mils |

Properties/Performance Values

- | | | | |
|-----------------------|------|--------------------|--------------|
| • Elongation at break | 35 % | • Tensile strength | 285 N/cm |
| | | | 162.7 lbs/in |



tesa® 53030

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=53030>