



tesa® 5008

Product Information



tesa® 5008 Multi-Purpose masking is a general purpose masking tape based on a fine crepe paper backing and a natural rubber adhesive.

Product Description

tesa® 5008 is a conformable masking tape based on a fine crepe paper backing coming in beige color and a natural rubber adhesive. The multi-purpose masking tape is suitable for light duty spray painting and general purpose applications like, holding, sealing, fixing. It provides a temperature resistance up to 176°F (80°C) for subsequent oven drying.

Product Features

- The beige crepe paper backing ensures a good conformability.
- The natural rubber adhesive system features good adhesion to multiple surfaces as well as a good tack.
- The multi-purpose masking tape offers excellent paint anchorage, making it suitable for light duty spray painting.

Application Fields

- tesa® 5008 is suitable for light duty spray painting and multi-purpose masking applications.
- It provides temperature resistance up to 176°F (80°C) for subsequent oven drying.
- The tape is hand-tearable.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------------------|-------------------|----------|
| • Backing | slightly-creped paper | • Total thickness | 135 µm |
| • Type of adhesive | natural rubber | | 5.3 mils |

Product Assortment

- | | |
|--------------------|-------|
| • Available colors | beige |
|--------------------|-------|

Properties/Performance Values

- | | | | |
|-----------------------|-------------|-----------------------------------|-----------|
| • Elongation at break | 6 % | • Hand tearability | very good |
| • Tensile strength | 27 N/cm | • Temperature resistance (60 min) | 80 °C |
| | 15.4 lbs/in | | 176 °F |

Adhesion to Values

- | | |
|---------|------------|
| • Steel | 3.8 N/cm |
| | 34.7 oz/in |

For latest information on this product please visit <http://l.tesa.com/?ip=05008>



tesa[®] 5008

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=05008>