


tesa® GlossGuard 50560 PV2 GlossGuard



Product Information

Temporary protection film for sensitive exterior automotive surfaces such as plastic parts made of PMMA

Product Description

tesa® 50560 PV2 GlossGuard is a premium grade self-adhesive film that has been developed for the protection of sensitive automotive plastic surfaces, e.g. B-pillar covers made of high gloss plastic such as PMMA, SAN, ABS, or similar. Due to good UV resistance and perfect paint compatibility tesa® 50560 PV2 GlossGuard is a reliable way to protect unpainted plastic components during the transportation process.

Main features

- Cost saving due to reduction in rectification and final repair
- Preserves the plastic finish, up to 12 months' storage outdoors
- Good adhesion to the range of plastic surfaces
- No special equipment needed, ensuring simple, low-cost application and removal processes
- Easy disposal. Both film and adhesive system are environmentally friendly

Application Fields

tesa® 50560 PV2 GlossGuard is suitable for the protection of painted automotive plastic parts made of PMMA, like B-pillar covers, against dirt and scratches during assembly, transport, and storage.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------------|-------------------|--------|
| • Backing | polyolefinic film | • Total thickness | 52 µm |
| • Type of adhesive | PIB | | 2 mils |

Properties/Performance Values

- | | | | |
|-----------------------|------------------------|----------------------------|----------|
| • Tensile strength | 22 N/cm
12.6 lbs/in | • Suitable for die cutting | yes |
| • Chemical Resistance | very good | • UV-resistance | 52 weeks |
| • Easy to remove | yes | | |

tesa® GlossGuard 50560 PV2 GlossGuard

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=50560PV2>