

tesa® 54190

Precision Die Cuts



Product Information

High performance decorative film for Black Out Design and Permanent Protection of sensitive surfaces

Product Description

The self adhesive tape consists of a black PVC film coated with a pure acrylic adhesive. tesa® 54190 can be applied for exterior and interior decorative purposes in the automotive industry.

The product features perfect optical appearance and long lasting adhesion properties. It can also be applied for the permanent protection of car parts from mechanical damage as well as to seal holes in the car body work. The film can be shaped when heated and can also be used on 3D-surfaces.

Application Fields

tesa® 54190 is designed for exterior and interior decorative application and permanent protection around the car body. This tape has a perfect visual appearance and long lasting adhesion properties on painted surfaces.

The product is also perfectly suitable for BSR-Applications.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	PVC film	• Color	black
• Type of adhesive	acrylic	• Color of liner	white
• Type of liner	PE-coated paper	• Weight of liner	138 g/m ²
• Total thickness	185 µm 7.3 mils		

Properties/Performance Values

• Elongation at break	250 %	• Chemical Resistance	very good
• Tensile strength	60 N/cm 34.3 lbs/in	• Matt surface finish	yes
• Abrasion resistance	good		

Additional Information

tesa® 54190 can be supplied individually to customer specification in various dimensions. Under the product number tesa® 7190, the material is also available as rolls.

tesa® 54190

Precision Die Cuts

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=7190DC>