

tesa® Professional 60950 / 60952

Product Information



Anti Slip tape - black

Product Description

The application area for tesa® Anti Slip Professional range is everywhere safe footing is required. Anti Slip black is the ideal protection to prevent from skidding and therefore helps to avoid accidents in the job related. Very good adhesion of the product is suitable for demanding surfaces such as factory floors, industry areas etc. The strong and durable adhesive coating secures a high Anti Slip effect of up to 1- 2 years in normal use areas. The Anti Slip tapes are hand tearable and no shrinkage occurs after application.

Application Fields

- Indoor and outdoor applications
- Applications in which a secure grip underfoot is required
- Fluorescent (tesa® 60953): stays bright for a long period for safety and warning purposes in dark rooms
- Transparent (tesa® 60952): make valuable surfaces such as wooden stairs, for example, safe unobtrusively
- Black-yellow (tesa® 60951): marking of very slippery surfaces

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	PVC film coated with mineral particles	• Thickness of liner	180 µm 7.1 mils
• Type of adhesive	acrylic	• Thickness of tape	720 µm 28.3 mils
• Total thickness	900 µm 35.4 mils		

Properties/Performance Values

• Elongation at break	25 %	• Fluorescent	no
• Tensile strength	30 N/cm 17.1 lbs/in	• Hand tearability	good
• Chemical Resistance	good	• Suitable for die cutting	yes
• Easy to remove	no		

Adhesion to Values

• Steel	5.8 N/cm 53 oz/in
---------	----------------------

tesa® Professional 60950 / 60952

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60950PRO>