




# tesa® 50560 PV0 Bumperfilm



## Product Information

Temporary protection film for unpainted or painted automotive exterior plastic surfaces

## Product Description

tesa® 50560 PV0 Bumperfilm is a premium grade self-adhesive film that has been developed for the protection of sensitive plastic surfaces, e.g. car bumpers.

Due to good UV resistance and perfect paint compatibility tesa® 50560 PV0 Bumperfilm is a reliable way to protect unpainted automotive plastic components during the transportation process.

Main features:

- Preserves the surface finish, up to 6 months' storage outdoors
- Thick material quality for high protection
- Suitable for die cutting and printing
- Cost saving due to reduction in rectification and final repair
- No special equipment needed, ensuring simple, low-cost application and removal processes
- Good adhesion to the range of paint finishes, even during transportation (tested at speeds higher than 160 km/h / 100 mph)
- Easy disposal. Both film and adhesive system are environmentally friendly

## Application Fields

tesa® 50560 PV0 Bumperfilm is suitable for the protection against dirt and scratches during assembly, transport, and storage of unpainted or painted automotive plastic parts like car bumpers.

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                   |                   |        |
|--------------------|-------------------|-------------------|--------|
| • Backing material | polyolefinic film | • Total thickness | 75 µm  |
| • Type of adhesive | PIB               |                   | 3 mils |

## Properties/Performance Values

- |                            |           |                       |            |
|----------------------------|-----------|-----------------------|------------|
| • Easy to remove           | yes       | • Tensile strength    | 16 N/cm    |
| • Suitable for die cutting | yes       |                       | 9.1 lbs/in |
| • UV resistance            | 24 week/s | • Chemical resistance | very good  |



# tesa<sup>®</sup> 50560 PV0 Bumperfilm

Product Information

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=50560>