

tesa® 68144

Product Information

100 μm/3.9 mils double-sided splicing tape

Product Description

tesa $^{\circ}$ 68144 is a 100 μ m/3.9 mils translucent double-sided splicing tape consisting of a non-woven carrier coated with an acrylic adhesive, covered by a white paper liner. The special adhesive formulation ensures a secure bond on a variety of paper materials, even at elevated temperatures.

Application Fields

Splicing of

- Paper (liner and flute) in corrugated board production
- · Paper in newsprint and converting processes
- · Lightweight cardboard

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing material	non-woven	•	Total thickness	100 μm
•	Type of adhesive	acrylic			3.9 mils
•	Type of liner	PE-coated paper	•	Color	translucent
			•	Color of liner	white

Properties/Performance Values

•	Temperature resistance long	70 °C	•	Temperature resistance short	100 °C
	term	158 °F		term	212 °F

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.