

# tesa® 4421

## product information



Medium grade masking tape up to 95°C / 203°F

tesa® 4421 provides an excellent blend of value and performance due to its excellent paper strength, cured rubber adhesive, and high shear. tesa® 4421 performs under stress and temperatures where general-purpose products fail. It also has excellent wet grab and should be used when general-purpose masking tapes do not perform adequately.

### Main Application

- Medium temperature masking applications
- Medium-duty bundling, holding, packaging, and splicing

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Technical Data

• Backing material	slightly-creped paper	• Elongation at break	10 %
• Total thickness	147.32 µm	• Tensile strength	36.8 N/cm
• Type of adhesive	natural rubber		

#### Adhesion to

• steel	3.7 N/cm 33.8 oz/in
---------	------------------------

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=04421>