

tesa® 64613

Product Information

Utility grade duct tape

Product Description

tesa® 64613 is a high shear and high tensile poly-coated cloth tape providing easy hand-tearability and adhesion to a variety of different surfaces. It shows easy unwind and tears straight properties. Excellent for a variety of packaging, bundling and repair applications.

Application Fields

- · Sealing of ducts
- · Fastening of protection films
- · Sealing of rubbish bags
- · Fixing, closing, packaging and a lot more!

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing material	PE laminated cloth	•	Total thickness	190 µm
•	Type of adhesive	natural rubber			7.5 mils

Properties/Performance Values

• EI	longation at break	16 %	•	Mesh	27 per square inch
• Te	ensile strength	39 N/cm	•	Straight tear edges	good
		22.3 lbs/in	•	Water resistance	medium
• H	land tearability	good			

Adhesion to Values

• Steel	4.95 N/cm
	45.2 oz/in



tesa® 64613

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

