

tesa® 54715 Noise Blocker Standard

Product Information



Optimum acoustic insulation die cut for permanent automotive hole covering applications

Product Description

tesa® 54715 Noise Blocker combines a mineral filled polyolefin layer with a powerful acrylic adhesive. This product is optimized for the automotive industry to securely cover holes that require excellent acoustic insulation in combination with good sealing properties.

Main features:

- Excellent acoustic insulation due to high area density 1.8kg/m²
- Secure adhesion on almost all substrates
- Good sealing properties

Application Fields

tesa® 54715 is especially suitable at the assembly line for interior hole covering on all car body areas, e.g. pillars, rocker, front/rear floor.

To ensure the highest performance possible, our aim is to fully understand your application (including the substrates involved) in order to provide the right product recommendation.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Backing materialType of adhesiveType of liner	polyolefin modified acrylic glassine	•	Total thickness Color	1140 μm 44.9 mils gray
Properties/Performance Values				
Chemical resistanceFlame resistance	good self-extinguishing		Puncture resistance Temperature resistance (30 min)	215 N 100 °C

Additional Information

tesa[®] 54715 can be supplied as die-cuts in roll or sheets individually to customer specific dimensions. Our application process engineers support with customized equipment and self-designed application tools to enhance productivity.

212 °F



tesa® 54715 Noise Blocker Standard

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 – as of 03/13/23 – en-TT