

tesa® 53499

Product Information



Premium strength tear tape

Product Description

tesa® 53499 combines our strongest tensilized polypropylene backing with synthetic rubber adhesive.

tesa® 53499 tear tape has good initial tack, excellent shear resistance and strong ultimate adhesion.

The product features excellent adhesion to highly recycled cardboard.

Application Fields

- · Heavy duty tear tape for corrugated and solid cardboard applications
- Excellent adhesion to large variety of cardboard qualities
- Recommended for automated application processes

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing material	TPP	•	Total thickness	180 μm
•	Type of adhesive	synthetic rubber			7.1 mils

Properties/Performance Values

•	Elongation at break	35 %	•	Tensile strength	450 N/cm
					257 lbs/in

Adhesion to Values

•	Steel	10.5 N/cm
		95.9 oz/in



tesa® 53499

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

