



Product Information



Mounting of thin photopolymer plates on compressible sleeves

Product Description

tesa® 52916 is especially designed for plate mounting of thin photopolymer plates (e.g. 1.14 mm / 0.045" or 1.70 mm / 0.067") on compressible sleeves in flexographic printing.

It is a double-sided tape with differentiated adhesion levels on its two sides.

While the sleeve side adhesive ensures a secure bond to the sleeve, the plate side adhesive is especially tailored for a strong bond to photopolymer plates, while at the same time allowing for easy repositioning and removal of the plate. All of our products for plate mounting on compressible sleeves feature very thin film backings to not interfere with the compressible characteristics of the sleeve.

Application Fields

Plate mounting of thin photopolymer plates (e.g. 1.14 mm / 0.045" or 1.70 mm / 0.067") on compressible sleeves in flexographic printing.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing material	PET film	•	Type of liner	glassine
•	Type of adhesive	acrylic			

Properties/Performance Values

Thickness category 100

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



²age 1 of 1 – as of 02/25/23 – en-TT