



tesa® 50565

Product Information



Strong 50µm/2 mils aluminium tape with and without liner (PV1 and PV0)

Product Description

tesa® 50565 is a strong aluminium tape, based on a 50µm/2 mils aluminium foil and an acrylic adhesive. tesa® 50565 is mainly used in the appliance industry and also for a wide range of other applications.

Features:

- good adhesion
- mechanical resistance
- moisture resistant
- vapour tight
- high thermal conductivity
- oil & acid resistant
- ageing-resistant
- available without liner (PV0) and with liner (PV1)
- flame retardant (UL510)

Application Fields

- Mounting of refrigeration coils
- General purpose temperature insulation
- Sealing of ducts
- Masking, protecting, repairing, closing ...and a lot more!

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------|----------------------|-------------------|
| • Type of liner | paper | • Total thickness | 90 µm |
| • Backing material | aluminum foil | • Color of liner | 3.5 mils
white |
| • Type of adhesive | acrylic | • Thickness of liner | 65 µm
2.6 mils |

Properties/Performance Values

- | | | | |
|-------------------------------|----------------------|-------------------------------|------------------|
| • Elongation at break | 8 % | • Hand tearability | good |
| • Tensile strength | 35 N/cm
20 lbs/in | • Operation temperature from | -40 °C
-40 °F |
| • Backing appearance (visual) | reflective | • Operation temperature up to | 160 °C
320 °F |

For latest information on this product please visit <http://l.tesa.com/?ip=50565>



tesa[®] 50565

Product Information

Adhesion to Values

- Steel 6 N/cm
54.8 oz/in

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=50565>