



# tesa<sup>®</sup> 64662

## Product Information

### Industrial Grade Poly-coated Cloth Duct Tape

#### Product Description

tesa<sup>®</sup> 64662 offers excellent tensile strength and hand-tearability. tesa<sup>®</sup> 64662 is available in a variety of colors. Excellent for draping, and securing as well as for demanding packaging, bundling, holding, seaming, sealing, protecting, wrapping and repairing applications.

#### Application Fields

- Patching
- Packaging
- Seaming
- Sealing

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Product Construction

- |                    |                    |                   |          |
|--------------------|--------------------|-------------------|----------|
| • Backing material | PE laminated cloth | • Total thickness | 230 µm   |
| • Type of adhesive | natural rubber     |                   | 9.1 mils |

#### Properties/Performance Values

- |                       |                      |                       |                    |
|-----------------------|----------------------|-----------------------|--------------------|
| • Elongation at break | 16 %                 | • Mesh                | 27 per square inch |
| • Tensile strength    | 42 N/cm<br>24 lbs/in | • Straight tear edges | good               |
| • Abrasion resistance | medium               | • Water resistance    | medium             |
| • Hand tearability    | good                 |                       |                    |

#### Adhesion to Values

- |         |                        |
|---------|------------------------|
| • Steel | 5.472 N/cm<br>50 oz/in |
|---------|------------------------|



# tesa<sup>®</sup> 64662

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=64662>