



# SPECIALTY TAPES FOR FILM CONVERTING





Splicing and Auxiliary Assortments

# tesa® EasySplice FilmLine ASSORTMENT



Product	tesa® EasySplice 51910 FilmLine PLUS	tesa® EasySplice 51918 FilmLine Black S	tesa® EasySplice 51948 FilmLine Black X	tesa® EasySplice 61958 FilmLine Black A
Main product features	<ul style="list-style-type: none"> <li>High tack contact adhesive</li> <li>Paper backing</li> </ul>	<ul style="list-style-type: none"> <li>High tack contact adhesive</li> <li>Black PET backing</li> <li>Improved wetting properties</li> </ul>	<ul style="list-style-type: none"> <li>Very high tack contact adhesive</li> <li>Black PET backing</li> <li>Excellent wetting properties</li> </ul>	<ul style="list-style-type: none"> <li>High tack contact adhesive</li> <li>Black PET backing</li> <li>Adhesion strip technology</li> </ul>
Customer benefits	<ul style="list-style-type: none"> <li>Secure splice performance even at high speeds on:                             <ul style="list-style-type: none"> <li>Standard non-polar films</li> <li>No need for scissors or cutters</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>Secure splice performance on:                             <ul style="list-style-type: none"> <li>Thick films</li> <li>Sharp edge films</li> <li>Tubular bags</li> <li>Easy splice detection</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>Secure splice performance even at high speeds on:                             <ul style="list-style-type: none"> <li>High slip films</li> <li>Non-woven materials</li> <li>Recycled film materials</li> <li>Easy splice detection</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>Secure splice performance on standard films</li> <li>Easy splice detection</li> <li>Less waste - no splitting mechanism</li> </ul>
Backing	Paper	PET	PET	PET
Color	●	●	●	●
Tack	●●●	●●●	●●●●	●●●
Thickness w/o liner [µm/mil]	115 / 4.5	105 / 4.1	110 / 4.3	105 / 4.1
Adhesion	●●●	●●●	●●	●●●
Shear resistance	●●●	●●●	●	●●●
Hand tearable	Yes	No	No	No
Tensile strength [N/cm]	30	70	70	70

# COMPLEMENTARY TAPES



	Tape description	Thickness [µm/mil]	Adhesive	Backing	Color
<b>End tabbing</b>					
tesa® 4124	Single-sided tape	65 / 2.6	Natural rubber	PVC	● ● ● ● ● ●
tesa® 4104	Colored single-sided tape	67 / 2.6	Natural rubber	PVC	● ● ● ● ● ● ● ● ● ●
<b>Failure flagging</b>					
tesa® 4104	Colored single-sided tape	67 / 2.6	Natural rubber	PVC	● ● ● ● ● ● ● ● ● ●
<b>Roller wrapping and belting</b>					
tesa® Printer's Friend 4863	Embossed surface	620 / 24.4	Natural rubber	Silicone-coated cloth	●
tesa® Printer's Friend 4563	Smooth surface	380 / 15	Natural rubber	Silicone-coated cloth	●
tesa® 4820	Single-sided PTFE tape	100 / 3.9	Silicone	PTFE	●
tesa® 4830*	Single-sided PTFE tape	160 / 6.3	Silicone	PTFE	●
<b>Core starting</b>					
tesa® 51194	Splittable double-sided tape	120 / 4.7	Synthetic rubber	Splittable paper	●
tesa® 4104	Colored single-sided tape	67 / 2.6	Natural rubber	PVC	● ● ● ● ● ● ● ● ● ●
tesa® 64620	Double-sided tape	185 / 7.3	Synthetic rubber	PP	●
tesa® 52307*	Double-sided tape	70 / 2.8	Acrylic	PVC	●
tesa® 51904	Double-sided tape	110 / 4.3	Natural rubber	Non-woven	●
tesa® 4985	Transfer tape	50 / 2	Acrylic	None	●

# CONVENTIONAL SPLICING TAPES

Application	Flying splice	Static splice	Flying splice / Static splice	Static splice	Static splice	Static splice	Splitting labels	Aluminum detection labels	Black detection labels
Product	tesa® 51904	tesa® 64620	tesa® 4200	tesa® 61127*	tesa® 4137	tesa® 4985	tesa® 54242*	tesa® 51003*	tesa® 51005*
Tape description	Double-sided tape	Double-sided tape	Double-sided tape	Single-sided tape	Single-sided tape	Transfer tape	Single-sided die cut	Aluminum label for inductive detection	Black label for optical detection
Main product features	<ul style="list-style-type: none"> <li>Paper backing</li> <li>High tack synthetic rubber adhesive</li> <li>Pink color</li> </ul>	<ul style="list-style-type: none"> <li>PP backing</li> <li>High tack solvent-free adhesive</li> <li>White color</li> </ul>	<ul style="list-style-type: none"> <li>PET Backing</li> <li>High tack silicone adhesive</li> <li>High temperature resistance</li> <li>Red color</li> </ul>	<ul style="list-style-type: none"> <li>PET Backing</li> <li>High tack silicone adhesive</li> <li>High temperature resistance</li> <li>Black color</li> </ul>	<ul style="list-style-type: none"> <li>Metalized backing</li> <li>High shear strength</li> <li>High temperature and ageing resistance</li> </ul>	<ul style="list-style-type: none"> <li>Modified acrylic adhesive</li> <li>High temperature resistance</li> <li>Transparent</li> </ul>	<ul style="list-style-type: none"> <li>High adhesion on various film materials</li> <li>Perforated breaking point</li> <li>Die cut on roll</li> </ul>	<ul style="list-style-type: none"> <li>Aluminized paper backing</li> <li>Die cut on roll</li> </ul>	<ul style="list-style-type: none"> <li>Black paper backing</li> <li>Die cut on roll</li> </ul>
Customer benefits	<ul style="list-style-type: none"> <li>Secure splice performance on standard non-polar substrates, even at high speeds</li> <li>No need for scissors or cutters</li> <li>Easy splice detection</li> </ul>	<ul style="list-style-type: none"> <li>Secure splice performance on standard films and at low speeds</li> </ul>	<ul style="list-style-type: none"> <li>Best splice performance on various siliconized substrates even at high speeds</li> <li>Easy splice detection</li> </ul>	<ul style="list-style-type: none"> <li>Best splice performance on various siliconized substrates even at high speeds</li> <li>Easy splice detection</li> </ul>	<ul style="list-style-type: none"> <li>Easy splice detection by light and heat radiation</li> </ul>	<ul style="list-style-type: none"> <li>Easy automatic application</li> <li>Excellent conformability on substrate</li> </ul>	<ul style="list-style-type: none"> <li>Easy top sheet fixation for conventional flying splice</li> </ul>	<ul style="list-style-type: none"> <li>Easy splice detection</li> </ul>	<ul style="list-style-type: none"> <li>Easy splice detection</li> </ul>


\* available upon request, please contact your tesa sales specialist

# EXPERTISE BY YOUR SIDE


Increasing demands on product quality and production efficiency as well as a market need for a wide range of different film materials call for a reliable partner for film converting processes. With over 125 years of experience as a global supplier of adhesive solutions and as the inventors of tesa® EasySplice for integrated flying splices, we are your reliable partner for film converting excellence.

## tesa® EasySplice FilmLine

With the invention of tesa® EasySplice, we revolutionized paper production and converting industry processes. Reliable splicing at the highest speeds combined with easy and fast job preparation was made possible, resulting in maximized process efficiency. Our tesa® EasySplice FilmLine assortment is specifically developed for film converters. The combination of tailored contact adhesives, reliable splitting strip solutions, and distinct product backings provides outstanding splice performance even on critical non-polar film materials.




### Fast and Easy Splice Preparation




**Underneath**  
Apply the tape under the top layer of the film reel. Then remove the upper part of the liner.



**On top**  
Attach the top layer onto the exposed adhesive of the tape.



**Remove**  
Tear off the excess film following the line of the remaining section of the liner.



**Finish**  
Before accelerating the reel carefully remove the lower part of the liner.



#### Save time

For reel preparation, apply just one straight line of tape – no extra tape, no additional split labels necessary.



#### Accelerate production

Run even difficult-to-splice substrates at full machine speed.



#### Reduce waste

Higher splice performance means less waste! tesa® EasySplice FilmLine products ensure safe closure of the reel during acceleration and precise opening after contact.

# OUR VALUE PROPOSITION – YOUR BENEFITS



### Partnering to Solve Industry Challenges


Our dedicated team of more than 100 sales experts worldwide can help you improve overall efficiency by recommending solutions that optimize your existing set-ups. We are also happy to discuss specific product or testing needs whenever required and continuously strive to shape a business relationship of trust and reliability.



### Extensive R&D and Lab Support

Worldwide, we have 500 specialized R&D engineers transforming innovative ideas into new products and improving existing solutions. Customer needs, industry trends, as well as process and raw material innovations form the basis for our daily work to develop state-of-the-art solutions for the film producing, printing, and converting industries.

### A Global Partner



tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data mentioned above are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



02/2020



Our management system is certified according to the standards ISO 9001, ISO/TS 16949, and ISO 14001.

United States & Canada  
tesa tape, inc.  
5825 Carnegie Boulevard • Charlotte, NC 28209  
Phone: 1-800-426-2181  
Email: [marketing@tesatape.com](mailto:marketing@tesatape.com)

[tesatape.com](http://tesatape.com)