


AUTOMOTIVE PE FOAM TAPES STICKING TOGETHER FOREVER

It is All About Mounting!

Our double-sided polyethylene (PE) foam tapes consist of a PE foam carrier with adhesives on each side. They are an important mounting solution for automotive interior and exterior design elements thanks to their:

- · Excellent damping properties and shock resistance
- · Superior bonding strength
- Perfect compensation of design tolerances
- · High conformability to match irregular surfaces
- · Outstanding leverage of force resistance
- Ability to level out the different thermal expansion of smaller parts like emblem and parking distance control holder





Our PE foam tape product family

For different applications, we have tailor-made solutions. A complete range of various thicknesses provides high flexibility for gap-filling purposes.

The latest introduction – our primerless PE foam tape tesa® 64912 – helps customers eliminate the need for primer. Its high-performance adhesive enables bonding of low surface energy (LSE), like PP/EPDM surfaces, and medium surface energy (MSE), like ABS surfaces, without any primer.



Our PE foam tape product family

		Primerless grade	High temperature performance grade	High initial performance grade	General purpose grade
Thickness (μm)	1,600			tesa® 62936	
	1,500				
	1,400				
	1,300				
	1,200	tesa® 64912	tesa® 62856		
	1,100				
	1,000				tesa® 62510
	900		tesa® 62855		
	800		tesa® 62708	tesa® 62934	tesa® 62508, tesa® 66108
	700				
	600			tesa® 62906	
	500		tesa® 62852	tesa® 62932	
	400			tesa® 62904	
	300				
Characteristics	Initial tack	even at 5°C			
	Peel adhesion				
	Temperature resistance		••••		
	Primer	No need	Yes, for LSE materials like PP/EPDM	Yes, for LSE materials like PP/EPDM	Yes, for LSE materials like PP/EPDM
Applications	Exterior parts: PDC, emblem, entry trim	Excellent holding power on plastic and clear coat Superior pushout performance Deep black color for design flexibility			
	Mirrors: exterior and interior mirror			Splintering protection Gap filling for curved base plate: Low thickness deviation	S
	Automotive electronics: instrument cluster		Gap filling and sealing Excellent cushioning properties Mounting on uneven surfaces		
	Glass: locator pin		No sliding and no creep		
	Interior parts: decorative trim	Mounting of interior plastic without primer		Ideal for rough or irregular surfaces	Gap filling and sealing

•••• Excellent ••• Very good •• Good • Adequate

Our products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless, we can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether our product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical staff will be glad to support you.