




tesa® Bumperfilm 50560 PV1



Product Information

Temporary protection tape for exterior plastic components

Product Description

tesa® Bumperfilm 50560PV1 is the best protection solution mainly for painted but also for unpainted plastic components. Applied after the manufacturing process, tesa® Bumperfilm 50560PV1 provides reliable protection for plastic surfaces susceptible to damage.

Due to the good UV-resistance and perfect paint compatibility tesa® Bumperfilm 50560PV1 is the most reliable way to protect painted plastic components during the transportation process.

Features & benefits:

- Reliable protection
- Secure adhesion during transport
- Cost savings as polishing or repair after demasking is eliminated
- Protection during outdoor storage up to 12 months
- Easy to apply and remove
- Easy disposal - both the film and the adhesive system are environmentally friendly

Application Fields

- Protection of plastic components during the assembly, storage and transportation process

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------------|-------------------|--------|
| • Backing material | polyolefinic film | • Total thickness | 52 µm |
| • Type of adhesive | PIB | | 2 mils |

Properties/Performance Values

- | | | | |
|-----------------------|------------------------|----------------------------|----------|
| • Tensile strength | 22 N/cm
12.6 lbs/in | • Suitable for die cutting | Yes |
| • Chemical resistance | very good | • UV resistance | 52 weeks |
| • Easy to remove | Yes | | |



tesa[®] Bumperfilm 50560 PV1

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=50560>