

tesa[®] extra Power

BNR 56338, 56348, 56384, 56385, 56386, 56388, 56389, 56396, 56488, 56490

Product Construction

- | | | | |
|--------------------|---------------------------|-------------------|--------------------|
| • Backing material | PE-film with PET-filament | • Total thickness | 215 µm
8.5 mils |
| • Type of adhesive | synthetic rubber | | |

Product Properties/Performance Values

- | | | | |
|------------------------|---------|-----------------------------|---|
| • Humidity resistance | yes | • Application temperature | from 10 up to 50 °C |
| • UV-resistance | yes | • Tensibility | 19 % |
| • Residue free removal | no | • Tensile strength | 100 N/cm
57.1 lbs/in |
| • Writable | no | • Hand tearability | yes |
| • Area of use | Outdoor | • Suitable surfaces | Even wood, Tiles,
Most plastics, Glass,
Metal |
| • Waterproof | yes | • Adhesive strength | High adhesion |
| • Ozone resistance | yes | • Oil- and grease-resistant | yes |
| • Solvent free | yes | • UV-resistant | yes |
| • Tear resistant | yes | • Water resistance | yes |

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=56338>