




tesa® 4661

Product Information



Standard acrylic paste coated cloth tape

Product Description

tesa® 4661 is a strong acrylic paste coated cloth tape. It is based on a 148 mesh woven rayon fabric backing and a natural rubber adhesive.

tesa® 4661 is an all-round cloth tape for a wide range of applications, often used for belting of components.

Features:

- high adhesion, even on rough surfaces
- very high tensile strength
- abrasion-resistant
- available in 7 colours: black, white, grey, yellow, blue, red, green

Sustainable Aspects



For more information: <https://www.tesa.com/product-sustainability>

Application Fields

- Marking of wires and cables
- Bundling of pipes, profiles etc.
- Noise protection
- Harnessing
- Colour coding
- Securing of sharp edges
- Sealing of cartons, tins and tubes
- Belting of components, nails, screws, bicycle rims etc.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------------|--|--------|
| • Backing material | Acrylic-coated cloth | • Bio-based content of liner by weight (acc. EN 16785) | 60 % |
| • Type of adhesive | natural rubber | • Total thickness | 300 µm |

For latest information on this product please visit <http://l.tesa.com/?ip=04661>



tesa® 4661

Product Information

Properties/Performance Values

• Elongation at break	12 %	• Mesh	145 count per square inch
• Tensile strength	100 N/cm	• Straight tear edges	very good
• Abrasion resistance	very good	• Temperature resistance	140 °C
• Easy to write on	yes	(removability from aluminum after 30 min exposure)	
• Hand tearability	very good	• Water resistance	good

Adhesion to Values

• steel	5.8 N/cm
---------	----------

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04661>