



tesa® 51194

Product Information

Product Description

tesa® 51194 is a double-sided tape. It consists of a splittable paper backing, modified synthetic rubber adhesive and a PET-film based liner.

Colour: Pink

Product Features

- Special splittable backing leaves no open adhesive residues
- Splitting force especially adjusted to high grammage paper and board
- Very low deviation of the splitting force
- Very good adhesion even on PE- and PP-coated surfaces as well as on board
- High initial tack

Application Fields

tesa® 51194 is designed for core starting and end tabbing applications in the paper and liquid board packaging industry. It is especially suitable for PE- and PP-coated surfaces as well as for high grammage paper grades and board.

- Core starting: also compatible with automatic dispensers
- End tabbing: the splittable backing allows (semi-) automatic roll opening

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------|----------|
| • Backing material | Splittable paper | • Type of liner | PET film |
| • Type of adhesive | synthetic rubber | • Total thickness | 170 µm |

Properties/Performance Values

- | | | | |
|-----------------------------------|-----------|---------------------------|------|
| • Shelf life time (packed) < 25°C | 12 months | • Static shear resistance | good |
|-----------------------------------|-----------|---------------------------|------|



tesa® 51194

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51194>