



tesa® 4610 Duct Tape



Product Information

Basic duct tape

Product Description

tesa® 4610 is a low grade duct tape with basic tape features and an attractive performance profile. The PE backing is reinforced with an 18 mesh PET fabric and coated with a tacky synthetic rubber adhesive with a very good adhesion level on various substrates.

tesa® 4610 is a self-adhesive tape with properties for a wide range of applications.

Features:

- high initial tack
- good hand tearability
- good adhesion to multiple materials
- easy to unwind

Application Fields

- Sealing of ducts
- Fastening of protection films
- Sealing of rubbish bags
- Fixing, closing, packaging, and a lot more!

Duct tapes are mainly used as general multipurpose tapes in a huge range of applications. They have a high market share in the segments of construction sites, MRO, and consumer end-users.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing material	PE laminated cloth	• Total thickness	150 µm
• Type of adhesive	synthetic rubber	• Thickness of tape	_NULL µm



tesa[®] 4610

Duct Tape

Product Information

Properties/Performance Values

• Elongation at break	20 %	• Hand tearability	very good
• Tensile strength	30 N/cm	• Humidity resistance	good
• Abrasion resistance	low	• Mesh	18 threads/inch ²
• Ageing resistance (UV)	medium	• Straight tear edges	good
• Easy to remove	no	• Temperature resistance (30 min)	95 °C
• Easy to write on	no	• Temperature resistance	95 °C
• Fluorescent	no	(removability from aluminum	
• Fogging	low	after 30 min exposure)	
		• Temperature resistance short	60 °C
		term duration	
		• Water resistance	medium

Adhesion to Values

• steel	4.5 N/cm
---------	----------

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04610>