



tesa® On & Off 55225

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing material	polyamid	• Type of adhesive	synthetic rubber
--------------------	----------	--------------------	------------------

Properties/Performance Values

• Adhesive strength	High adhesion	• Open & Closable up to	10000 time(s)
• Applicationfield	Home, Office, Car, Garage	• Residue free removal	no
• Area of use	Indoor	• Reusable	no
• Batteries included	no	• Solvent free	yes
• Batteries required	no	• Spare part service	no
• Hand tearability	no	• Suitable surfaces	Even wood, Tiles, Most plastics, Metal, Steel
• Material	Polyamid	• UV-resistant	no

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=55225>