

# tesa® On & Off 55228

## **Product Information**

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

Backing material	polyamid	• Type of adhesive	synthetic rubber
Properties/Performance Values			
Adhesive strength	Very high adhesion	Open & Closable up to	1000 time(s)
<ul> <li>Applicationfield</li> </ul>	Home, Office, Car,	Residue free removal	no
	Garage	Reusable	no
Area of use	Indoor	Solvent free	yes
<ul> <li>Batteries included</li> </ul>	no	<ul> <li>Spare part service</li> </ul>	no
<ul> <li>Batteries required</li> </ul>	no	Suitable surfaces	Even wood, Tiles,
<ul> <li>Hand tearability</li> </ul>	no		Most plastics, Metal,
<ul> <li>Material</li> </ul>	Polyamid		Steel
		UV-resistant	no

#### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



<sup>2</sup>age 1 of 1 – as of 26/09/24 – en-ZA