



# tesa® 4288

## Product Information



Medium duty tensilised strapping tape

### Product Description

tesa® 4288 is an extremely stable, medium duty polypropylene strapping tape with a natural rubber adhesive system.

tesa® 4288 exhibits high tensile strength with low elongation at the same time. The applied product is highly heat- and cold-resistant and due to the black backing, extremely resistant to UV-light.

### Application Fields

Bundling of copper, iron and plastic pipes, palletising and coil tabbing.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

• Backing material	MOPP	• Total thickness	114 µm
• Type of adhesive	synthetic rubber	• Colour	black

### Properties/Performance Values

• Elongation at break	35 %	• No discolouration	yes
• Tensile strength	300 N/cm	• Residue free removal	yes

### Adhesion to Values

• steel	6 N/cm
---------	--------



# tesa® 4288

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04288>