

tesa® On & Off 56187 Flooring Tape Hook & Loop

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Type of adhesive	synthetic rubber	 Total thickness 	1000 µm
---	------------------	------------------	-------------------------------------	---------

Properties/Performance Values

•	Adhesive strength	High adhesion	•	Material	PP (polypropylene)
•	Applicationfield	Home	•	Residue free removal	no
•	Batteries included	no	•	Solvent free	yes
•	Batteries required	no	•	Suitable surfaces	Tiles, Brick, Most
•	Chemical resistance	no			plastics, Glass, Acrylic
•	Ecofriendly packaging	no			glass, Cardboard,
•	Humidity resistance	no			Plaster, Paper, Metal,
					Steel, Stone
			•	Tear resistance	yes
			•	Temperature resistance	no

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

