



tesa[®] extra Power 56339 Perfect

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing material	Acrylic-coated cloth	• Total thickness	310 µm
• Type of adhesive	natural rubber		

Properties/Performance Values

• Tensile strength	100 N/cm	• Ozone resistance	yes
• Adhesive strength	Very high adhesion	• Residue free removal	yes
• Ageing resistance (UV)	yes	• Reusable	no
• Application temperature from	+10 °C	• Solvent free	yes
• Application temperature to	+50 °C	• Spare part service	no
• Applicationfield	Home, Garden, Car, Garage	• Suitable surfaces	Even wood, Tiles, Brick, Most plastics, Glass, Acrylic glass, Cardboard, Plaster, Paper, Metal, Steel, Stone
• Area of use	In- and Outdoor		
• Batteries included	no	• Tear resistance	yes
• Batteries required	no	• Temperature resistance	yes
• Ecofriendly packaging	yes	• Temperature resistance max.	140 °C
• Hand tearability	yes	• Tensibility	13 %
• Hazard material	no	• UV-resistant	yes
• Humidity resistance	yes	• Water resistance	yes
• Oil and grease resistance	yes	• Waterproof	yes
		• Writable	yes



tesa[®] extra Power 56339 Perfect

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=56339>