

# tesa® 60418

## Product Information



### Sustainable Aspects



For more information: <https://www.tesa.com/product-sustainability>

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

• Backing material	PET	• synthetic rubber	None
• Recycled content of backing	85 %	• Total thickness	36 µm

### Product Assortment

• Available colors	white, transparent, brown
--------------------	------------------------------

### Properties/Performance Values

• Elongation at break	120 %	• Silent unwinding	no
• Tensile strength	38 N/cm	• Solvent free	yes
• Automatic application	yes	• Suitable for dangerous goods	no
• Hand tearability	no	• Suitable for deep freezing	no
• Packaging Weight	Up to 25 kg	• Transport Information	Temperature 0-35°C
• Printability	no		

### Adhesion to Values

• steel	6 N/cm
---------	--------

### Certificates

#### Sustainability Certificates

- Tested according to INGEDE method 12 at an independant institute.
- Recycled content certified by an independant institute according to UNI EN ISO 14021:2021

# tesa® 60418

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60418>