


tesa® 58362

Product Information



Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing material	PET	• Total thickness	100 µm
• Type of adhesive	tackified acrylic	• Colour	transparent
• Type of liner	glassine	• Colour of liner	brown/blue logo

Properties/Performance Values

• Dielectric breakdown voltage	9800 V	• Temperature range	-40~125 °C
• Static shear resistance at 23°C	very good	• Temperature resistance	very good
• Static shear resistance at 40°C	very good	• Temperature resistance long term duration	125 °C
• Static shear resistance at 70°C	very good		

Adhesion to Values

• Aluminium (initial)	5.7 N/cm	• Steel (initial)	7 N/cm
• PC (initial)	6.7 N/cm	• Steel (after 14 days)	8.5 N/cm

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=58362>