

tesa® PRO 74613

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing material	PE-film with PET-filament	• Total thickness	175 µm
• Type of adhesive	synthetic rubber		

Product Assortment

• Available colors	black, grey
--------------------	-------------

Properties/Performance Values

• Elongation at break	14 %	• Residue free removal	no
• Tensile strength	40 N/cm	• Salt water resistance	medium
• Abrasion resistance	good	• Solvent free	yes
• Adhesive strength	High adhesion	• Tear resistance	yes
• Ageing resistance (UV)	medium	• Temperature resistance	medium
• Chemical resistance	medium	• Tensibility	14 %
• Hand tearability	good	• Water resistance	low
• Humidity resistance	medium	• Waterproof	yes
• Oil and grease resistance	no	• Writable	no

Adhesion to Values

• rough surfaces	5.5 N/cm
------------------	----------

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=74613PRO>