


tesa® 60412

Product Information



Sustainable Aspects

- Backing made with 90% recycled PET from post consumer waste
- Solvent-free production process
- Recycling friendly adhesive does not disturb the paper recycling process



For more information: <https://www.tesa.com/product-sustainability>

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing material	PET	• Type of adhesive	water-based acrylic
• Bio-based carbon content of liner (acc. DIN EN 16640)	90 %	• Total thickness	56 µm

Product Assortment

• Available colors	transparent, white, brown
--------------------	---------------------------

Properties/Performance Values

• Elongation at break	130 %	• Packaging Weight	Up to 30 kg
• Tensile strength	60 N/cm	• Printability	very good
• Automatic application	no	• Silent unwinding	yes
• Hand tearability	low	• Suitable for deep freezing	yes
• Humidity resistance	yes	• Transport Information	Temperature 0-70°C

Adhesion to Values

• steel	3 N/cm
---------	--------

Certificates

Sustainability Certificates

- Tested according to INGEDE method 12. Test report available

tesa® 60412

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60412>