

tesa® 52995

Product Information



Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing material	PU film	• Total thickness	280 µm
• Type of adhesive	acrylic	• Colour	transparent
• Type of liner	PET	• Colour of liner	translucent

Product Assortment

• Available formats	LOG ROLL TRIMMED
---------------------	------------------

Properties/Performance Values

• Tensile strength	50 N/cm	• Printability	no
• Abrasion resistance	yes	• Scratch resistance	very good
• Chemical resistance	very good	• Suitable for die cutting	yes
• Conformability	very good	• Temperature resistance	yes
• Glossy surface finish	yes	• Temperature resistance (30 min)	90 °C
• Matt surface finish	no		

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=52995PV0>