

# tesa<sup>®</sup> Powerbond

## Product Information



55714

### Product Features

- Slim, only 9 mm wide
- \* Ideal for fixation of cable ducts, small decorations, LED-bars
- \* Strong hold on both sides
- \* Individually cuttable
- \* Partly conformable to the surface
- \* Only use on dry, clean and grease free surfaces
- \* Do not use on sensitive surfaces, damp areas or outdoor
- \* Do not apply under 10°C. Temperatures above 40°C reduce adhesive strength

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |         |                   |         |
|--------------------|---------|-------------------|---------|
| • Backing material | PE foam | • Total thickness | 1000 µm |
| • Type of adhesive | acrylic |                   |         |

### Properties/Performance Values

- |                                |   |                        |   |
|--------------------------------|---|------------------------|---|
| • Ageing resistance (UV)       | yes   | • Humidity resistance  | no  |
| • Application temperature from | -10 °C  | • Residue free removal | no  |
| • Applicationfield             | Bedroom, Children's room, Hall, Home, Living room, Office, Bathroom | • Suitable surfaces    | Even wood, Tiles, Most plastics, Glass, Acrylic glass, Steel, Metal |
| • Chemical resistance          | no  |                        |   |

# tesa<sup>®</sup> Powerbond

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=55714>