

# tesa®

## Product Information

STARKES  
KLETTBAND FÜR  
DAUERHAFTE  
FIXIERUNG



55234

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

• Backing material	PE	• Total thickness	4600 µm
• Type of adhesive	acrylic	• Holding power up to	4 Kg

### Properties/Performance Values

• Adhesive strength	Very high adhesion	• Solvent free	no
• Applicationfield	Home, Office, Car, Garage	• Suitable surfaces	Tiles, Most plastics, Glass, Acrylic
• Area of use	In- and Outdoor		glass, Steel, Metal, Lacquered wood, Even lacquered wood
• Material	PP (polypropylene)		
• Residue free removal	no	• Temperature resistance	yes
		• UV-resistant	yes

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=55234>