

tesa®

Product Information

77778



Product Description

The adjustable adhesive nail is ideal to securely attach canvases & stretcher frames on sensitive surfaces, e.g. wallpaper & plaster. Comfortable to apply, removable without a trace and easily reusable. The adjustable adhesive nail is ideal to securely attach canvases & stretcher frames on sensitive surfaces, e.g. wallpaper & plaster. Comfortable to apply, removable without a trace and easily reusable.

Product Features

- Adjustable adhesive nail
- For sensitive, textured surfaces, e.g. wallpaper
- Ideal for mounting canvases and stretcher frames
- Holds objects of up to 1kg per nail (2kg for two nails)
- Easy On & Off: no tools, can be removed without a trace
- Reusable with new adhesive strip
- Adjustable adhesive nail
- For sensitive, textured surfaces, e.g. wallpaper
- Ideal for mounting canvases and stretcher frames
- Holds objects of up to 1kg per nail (2kg for two nails)
- Easy On & Off: no tools, can be removed without a trace
- Reusable with new adhesive strip

Application Fields

II

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|--------------------------------|------|
| • Type of adhesive | synthetic rubber | • Holding power of strip up to | 1 Kg |
|--------------------|------------------|--------------------------------|------|

Properties/Performance Values

- | | | | |
|--------------------------------|------------------|------------------------|-----|
| • Application temperature from | -15 °C | • Ozone resistance | no |
| • Chemical resistance | no | • Residue free removal | yes |
| • Hazard material | no | • Reusable | yes |
| • Humidity resistance | no | • UV-resistant | no |
| • Material | PS (polystyrene) | • Waterproof | no |
| • Oil and grease resistance | no | | |

tesa®

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=77778>