

tesa® extra Power

Product Information

56431, 56432

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing material	Acrylic-coated cloth	• Total thickness	280 µm
• Type of adhesive	natural rubber		

Properties/Performance Values

• Tensile strength	70 N/cm	• Residue free removal	yes
• Adhesive strength	High adhesion	• Solvent free	yes
• Ageing resistance (UV)	yes	• Suitable surfaces	Even wood, Tiles, Brick, Glass, Acrylic glass, Cardboard, Plaster, Paper, Metal, Steel, Stone
• Application temperature from	+10 °C		
• Application temperature to	+50 °C		
• Area of use	Outdoor		
• Hand tearability	yes		
• Humidity resistance	yes	• Tear resistance	yes
• Oil and grease resistance	no	• Temperature resistance	yes
• Ozone resistance	yes	• Tensibility	9 %
		• UV-resistant	yes
		• Water resistance	yes
		• Waterproof	no
		• Writable	yes

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=4671DIY>