

tesa[®] extra Power

Product Information

56343, 56341, 56342, 56344, 56339

Product Description

tesa cloth tape extra Power Perfect is a premium quality repair tape designed for demanding indoor and outdoor applications.

Product Features

- Cloth tape for all professional solutions like handicrafts, fastening, bundling, strengthening, marking and much more
- Very strong adhesive power, even on rough and oily surfaces
- For permanent high resilience and long-term results
- Weather-resistant cloth tape for in-and outdoor applications
- Tear-resistant but tearable by hand
- Can be written on
- Available in a wide range of colours

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------------|-------------------|--------|
| • Backing material | Acrylic-coated cloth | • Total thickness | 310 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|--------------------------------|--------------------|-------------------------------|--|
| • Tensile strength | 100 N/cm | • Solvent free | yes |
| • Adhesive strength | Very high adhesion | • Suitable surfaces | Even wood, Tiles, Brick, Most plastics, Glass, Acrylic glass, Cardboard, Plaster, Paper, Metal, Steel, Stone |
| • Ageing resistance (UV) | yes | | |
| • Application temperature from | +10 °C | | |
| • Application temperature to | +50 °C | | |
| • Area of use | In- and Outdoor | | |
| • Hand tearability | yes | • Tear resistance | yes |
| • Humidity resistance | yes | • Temperature resistance | yes |
| • Oil and grease resistance | yes | • Temperature resistance max. | 140 °C |
| • Ozone resistance | yes | • Tensibility | 13 % |
| • Residue free removal | yes | • UV-resistant | yes |
| | | • Water resistance | yes |
| | | • Waterproof | yes |
| | | • Writable | yes |

tesa[®] extra Power

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=4651DIY>