

tesa[®] extra Power

Product Information

56348, 56396, 56389, 56490, 56388

Sustainable Aspects

By incorporating > 60% post-consumer recycled (PCR) material into its backing component, tesa[®] extra Power Universal offers an increased recycled material content without compromising performance.

Properties/Performance Values

- | | | | |
|--------------------------------|-----------------|-------------------------|---|
| • Application temperature from | 5 °C | • Ecofriendly packaging | yes |
| • Application temperature to | 60 °C | • Suitable surfaces | Even wood, Tiles,
Most plastics, Glass,
Metal |
| • Area of use | In- and Outdoor | | |

Certificates

Certified according to

- UL ECVP 2809-2 (validity: 2024-02-26 to 2025-02-26, region(s): Solbiate con Cagno, Como, Italy)

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=60462DIY>