# tesa® 4262



## **Product Information**

### General purpose polypropylene carton sealing tape

General purpose polypropylene carton sealing tape. Suitable for use on recycled board and under shrink wrap. Operating temperature between -50°C and 100°C.

Available in hand rolls and machine rolls, in transparent and brown.

## Main Application

Packaging and carton sealing for light to medium cartons.

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Technical Data**

| • | Backing material | BOPP    | • | Elongation at break | 90 %     |
|---|------------------|---------|---|---------------------|----------|
| • | Total thickness  | 52 μm   | • | Tensile strength    | 123 N/cm |
| • | Type of adhesive | acrylic |   |                     |          |

#### **Properties**

Manual application Yes

#### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

