



# tesa<sup>®</sup> Adhesive Strips for Tiles & Metal 3kg



## Product Information

BNR 77761

## Product Description

Refill pack for the Adhesive Nail for Tiles & Metal 3kg. For convenient reuse of the Adhesive Nail or to use alone.

## Product Features

- Strip for reuse of the Adhesive Nail for Tiles & Metal 3kg
- For smooth and solid surfaces like tiles indoors
- For objects up to 3kg per strip
- Strip can also be used alone without a nail
- Removable without a trace

## Application Fields

How to apply – Step by step1. In order to ensure the best possible bond, clean the surface with a silicone-free window cleaner or methylated spirit. The surface should be completely dry before application.

2. The Adhesive Strip should be applied first to the rougher surface. Be careful not to touch the exposed adhesive area at any time.

3. Press down evenly over the entire strip for at least 5 seconds and then remove the protective foil.

4. Now apply your object or a tesa<sup>®</sup> Adhesive Nail by aligning it on the top of the strip and then folding it down. Press down evenly all over your entire object or the entire nail for at least 5 seconds.

5. The tab should be left accessible behind your object or under the nail for easy removal.

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                                |                  |                       |      |
|--------------------------------|------------------|-----------------------|------|
| • Type of adhesive             | synthetic rubber | • Holding power up to | 3 Kg |
| • Total thickness              | 650 µm           | • Silicone free       | yes  |
| • Holding power of strip up to | 3 Kg             |                       |      |



# tesa<sup>®</sup> Adhesive Strips for Tiles & Metal

## 3kg

### Product Information

#### Properties/Performance Values

|                                |                   |                               |  |
|--------------------------------|-------------------|-------------------------------|--|
| • Application temperature from | -15 °C            | • Residue-free removability   | yes  |
| • Area of use                  | Indoor            | • Reusable                    | no   |
| • Batteries included           | no                | • Reusable with               | _NULL  |
| • Batteries required           | no                | • Solvent free                | yes  |
| • Chemical Resistance          | no                | • Suitable surfaces           | Even wood, Tiles,<br>Most plastics, Glass,<br>Acrylic glass, Steel,<br>Metal |
| • Hazard material              | no                |                               |  |
| • Humidity resistance          | no                | • Temperature resistance max. | 35 °C  |
| • Material                     | PE (polyethylene) | • Temperature resistance min. | 5 °C   |
| • Oil and grease resistance    | no                | • UV resistant                | no   |
| • Ozone resistance             | no                | • Waterproof                  | no   |

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>