



tesa® Adjustable Adhesive Screw for Wallpaper & Plaster 1kg



Product Information

BNR 77775

Product Description

Height adjustable Adhesive Screw for up to 1kg. Perfect for mounting decorative objects on textured and sensitive surfaces like wallpaper or plaster.

Product Features

- For textured and sensitive surfaces like wallpaper or plaster
- Holds up to 1kg* per screw or 2kg using 2 screws
- Height adjustable for straight alignment
- Removable without a trace
- Reusable with a new strip

*For optimal results please read instruction leaflet

Application Fields

How to apply – Step by step1. Get the best out of each Adhesive Strip by cleaning the surface of dirt and dust with a dust-free cloth.

2. Apply the Adhesive Strip to the rougher surface, so in case of wallpaper or plaster always first apply it to the wall, with the blue tab facing the wall. Before application, make sure that your surface is strong enough to take the weight of the object you want to attach.

3. Press down evenly over the entire strip for at least 5 seconds and only then remove the protective foil. Pressing down like this means that the flexible polymer chains are activated to form U-shaped links with the surface. It's these links that give such a secure and reliable bond, so the harder and more evenly you press, the better the bond.

4. Now apply the tesa® Adjustable Adhesive Screw by aligning it on the top edge of the strip, then folding it down. Press down evenly all over the entire nail for at least 5 seconds.

5. The tab should be left accessible behind your object or below the screw for easy removal.

6. Push the red toggle up to unlock the nail head and adjust it to the desired position, then lock the head by pushing the red toggle back down until it clicks into place.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|--------------------------------|------|
| • Type of adhesive | synthetic rubber | • Holding power of strip up to | 1 Kg |
|--------------------|------------------|--------------------------------|------|



tesa® Adjustable Adhesive Screw for Wallpaper & Plaster 1kg

Product Information

Properties/Performance Values

• Application temperature from	-15 °C	• Ozone resistance	no
• Chemical Resistance	no	• Residue-free removability	yes
• Hazard material	no	• Reusable	yes
• Humidity resistance	no	• UV resistant	no
• Material	PS (polystyrene)	• Waterproof	no
• Oil and grease resistance	no		

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?cp=NaN>