



tesa[®] extra Power Extreme Outdoor

Product Information

BNR 56395

Product Description

Use tesa[®] extra Power Extreme Outdoor for all situations calling for an extremely weather resistant and waterproof repairing tape with extra high adhesion.

Product Features

- Extremely weather-resistant and waterproof, especially designed for outdoor applications
- 1 year UV-resistant (UV-treated PE film)
- For handicrafts, repairing, fastening, bundling, strengthening, marking and much more
- Temperature-resistant from -40°C to +95°C
- Hand-tearable
- Solvent-free

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------------|-------------------|--------|
| • Backing | PE extruded cloth | • Total thickness | 210 µm |
| • Type of adhesive | synthetic rubber | | |



tesa[®] extra Power Extreme Outdoor

Product Information

Properties/Performance Values

• Tensile strength	41 N/cm	• Residue-free removability	no
• Adhesive strength	Very high adhesion	• Reusable	no
• Ageing resistance (UV)	yes	• Solvent free	yes
• Application temperature from	+10 °C	• Spare part service	no
• Application temperature to	+50 °C	• Suitable surfaces	Even wood, Tiles, Most plastics, Glass, Acrylic glass, Cardboard, Paper, Metal, Steel
• Applicationfield	Home, Garden, Car, Garage		
• Area of use	Outdoor		
• Batteries included	no	• Tear resistance	yes
• Batteries required	no	• Temperature resistance	yes
• Ecofriendly packaging	no	• Temperature resistance max.	95 °C
• Hand tearability	yes	• Temperature resistance min.	-40 °C
• Hazard material	no	• Tensibility	23 %
• Humidity resistance	yes	• Transparency	medium
• Material	PE (polyethylene)	• UV resistant	yes
• Oil and grease resistance	no	• Water resistance	yes
• Ozone resistance	yes	• Waterproof	yes
		• Writable	no

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>