



tesa[®] extra Power Perfect

Product Information

BNR 56343, 56341, 56342, 56344, 56339

Product Description

tesa cloth tape extra Power Perfect is a premium quality repair tape designed for demanding indoor and outdoor applications.

Product Features

- Cloth tape all professional solutions like handicrafts, fastening, bundling, strengthening, marking and much more
- Highest and perfect adhesive power, also on rough and oily surfaces
- For permanent high resilience and long-term results
- Weather-resistant cloth tape for in-and outdoor applications
- Tear-resistant but tearable by hand
- Can be written on
- Available in a wide range of colours

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------------|-------------------|--------|
| • Backing | Acrylic-coated cloth | • Total thickness | 310 µm |
| • Type of adhesive | natural rubber | | |



tesa[®] extra Power Perfect

Product Information

Properties/Performance Values

• Tensile strength	100 N/cm	• Ozone resistance	yes
• Adhesive strength	Very high adhesion	• Residue-free removability	yes
• Ageing resistance (UV)	yes	• Reusable	no
• Application temperature from	+10 °C	• Solvent free	yes
• Application temperature to	+50 °C	• Spare part service	no
• Applicationfield	Home, Garden, Car, Garage	• Suitable surfaces	Even wood, Tiles, Brick, Most plastics, Glass, Acrylic glass, Cardboard, Plaster, Paper, Metal, Steel, Stone
• Area of use	In- and Outdoor	• Tear resistance	yes
• Batteries included	no	• Temperature resistance	yes
• Batteries required	no	• Temperature resistance max.	140 °C
• Ecofriendly packaging	yes	• Tensibility	13 %
• Hand tearability	yes	• UV resistant	yes
• Hazard material	no	• Water resistance	yes
• Humidity resistance	yes	• Waterproof	yes
• Oil and grease resistance	yes	• Writable	yes

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>