

tesa[®] Powerbutton Classic hook Square

Product Information

BNR 59332

Product Description

The tesa® Powerbutton Classic single hook square is an elegant metal hook for for damage-free mounting without drilling holes. It can hold weights of up to 6 kg

Product Features

- Easy application without drilling, screws or nails
- Extra-strong hold up to 6kg
- Strong hold on most surfaces1
- Usable on and removable from most surfaces2
- Waterproof
- High temperature resistance
- Made from stainless steel
- Do not rust
- Available as single, double or triple hooks
- Hooks reusable with the tesa® Powerbutton technology
- 1
- 2

¹ 1 Does not hold Plaster, Wallpaper, PE, PTFE or PP

² 2 Not removable from Plaster or Wallpaper. Residues might remain

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

 Type of adhesive 	Silane modified	 Hook shape 	Square
	polymer		
 Holding power up to 	6 Kg		



tesa[®] Powerbutton Classic hook Square

Product Information

Properties/Performance Values

•	Application temperature from	+15 °C
•	Application temperature to	+30 °C
•	Applicationfield	Bathroom, Kitchen
•	Area of use	Indoor
•	Batteries included	no
•	Batteries required	no
•	Chemical Resistance	no
•	Hazard material	no

- Humidity resistance
- Material
- Residue-free removability
- Reusable
- Solvent free
- Suitable surfaces
- UV resistant
- Waterproof

yes Stainless steel yes yes Glazed Tiles, Marble, Glass, Metal, Stone, Concrete, Even wood, Most plastics yes no

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

