



tesa® extra Power Transparent

Product Information



BNR 56349

Product Description

tesa® extra Power Transparent is a transparent self-adhesive foil duct tape for a wide range of surfaces. It is waterproof and weatherproof.

Product Features

- Excellent adhesion to many types of surfaces, rough or smooth
- Strong, ageing-resistant adhesive
- Weather- and waterproof
- Very good resistance to solvents
- Ideal for repairs on transparent plastic material and temporary repairs on cracked glass

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|-------------------|--------|
| • Backing | PE film | • Total thickness | 140 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------------------|--------------------|-----------------------------|--|
| • Tensile strength | 20 N/cm | • Residue-free removability | no |
| • Adhesive strength | Very high adhesion | • Solvent free | yes |
| • Ageing resistance (UV) | yes | • Suitable surfaces | Glass, Acrylic glass,
Most plastics |
| • Application temperature from | +10 °C | | |
| • Application temperature to | +50 °C | • Tear resistance | yes |
| • Area of use | Outdoor | • Temperature resistance | yes |
| • Hand tearability | yes | • Tensibility | 400 % |
| • Humidity resistance | yes | • UV resistant | yes |
| • Oil and grease resistance | no | • Water resistance | yes |
| • Ozone resistance | yes | • Waterproof | yes |
| | | • Writable | no |



tesa[®] extra Power Transparent

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>