



tesa® Adhesive Hook for Transparent & Glass 1kg



Product Information

BNR 77735

Product Description

Transparent Adhesive Hook holds up to 1kg per hook. Invisible mounting for decorations and medium weight objects on transparent and solid surfaces like glass.

Product Features

- For transparent and solid surfaces indoors
- For medium weight objects up to 1kg per hook
- Removable without a trace
- Reusable with a new strip
- Limited UV-resistant

Application Fields

How to apply – Step by step1. Clean the surface with silicone-free window cleaner or methylated spirit. Make sure the surface is dry before application

2. Apply the Adhesive Strip first to the rougher surface. Be careful not to touch the adhesive area at any time.

3. Apply the hook, also pressing on it evenly all over for at least 5 seconds.

4. Make sure the tab is accessible for easy removal.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------------------|------------------|-----------------|-------------|
| • Type of adhesive | synthetic rubber | • Hook shape | Rectangular |
| • Holding power of strip up to | 1 Kg | • Silicone free | yes |
| • Holding power up to | 1 Kg | | |



tesa® Adhesive Hook for Transparent & Glass 1kg

Product Information

Properties/Performance Values

• Application temperature from	-15 °C	• Residue-free removability	yes
• Area of use	Indoor	• Reusable	yes
• Batteries included	no	• Reusable with	Adhesive Strip 1,0kg
• Batteries required	no		Transparent
• Chemical Resistance	no	• Solvent free	yes
• Hazard material	no	• Suitable surfaces	Even wood, Tiles,
• Humidity resistance	no		Most plastics, Glass,
• Material	PS (polystyrene)		Acrylic glass, Steel,
• Oil and grease resistance	no		Metal
• Ozone resistance	yes	• Temperature resistance max.	35 °C
		• Temperature resistance min.	5 °C
		• UV resistant	yes
		• Waterproof	no

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>