

## tesa® Waterproof XL

**Product Information** 

BNR 40519

#### **Product Description**

tesa<sup>®</sup> Powerstrips Waterproof XL strips are a water-resistant adhesive solution great to mount objects in bathrooms and other humid areas. With a holding power of up to 3 kg per strip and its extra large size, they are ideal to securely fix objects to smooth surfaces and tiles. With tesa<sup>®</sup> Powerstrips Waterproof XL strips no need for drill or tools, they are clean, easy to use and can be removed without any trace. Powerstrips<sup>®</sup> Waterproof XL strips may be used on its own or to remount tesa<sup>®</sup> Lavaa and tesa<sup>®</sup> Baboo products.

#### **Product Features**

- tesa® Powerstrips Waterproof XL: Adhesive strips for fast, clean and easy mounting
- Self-adhesive strips for hanging and mounting objects in bathrooms of up to 3 kg
- · Specially developed for humid environments and usage directly in the shower and bathtub area
- · Clean installation: No need for drills or other tools to mount bathroom objects, no surface damage
- Residue-free removal: tesa® Powerstrips Waterproof XL strips can be easily removed and leave no traces behind
- Adheres to glazed tiles, marble, metal, glass, wood, and plastics (ABS, PS, Acrylic Glass)
- Not suitable for stone, cement, wallpaper, plaster, enamel varnish and plastics such as PP, PE and PTFE
- Refill strips for tesa<sup>®</sup> Lavaa shower baskets and tesa<sup>®</sup> Baboo storage boxes

#### **Application Fields**

Mounting

1. Clean the surface with alcohol or silicone-free glass cleaner

2. Wipe the waterproof primer over the surface using the primer tissue- wait for 10 seconds to allow the primer to evaporate

- 3. Attach the Powerstrips® Waterproof XL strip to the object press firmly for 5 seconds minimum
- 4. Remove the cover sheets from the Powerstrips®
- 5. Position the object on the surface press firmly towards the wall
- 6. Make sure the tab can be accessed for removal

#### Disassembly

1. First stretch the tab of the Powerstrip<sup>®</sup> to around 3-5 cm, hold object tight - don't press it on, and keep stretching the Powerstrip<sup>®</sup> parallel to the surface (do not pull strip away from the surface, as Powerstrip<sup>®</sup> may rip)

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

| • | Type of adhesive | synthetic rubber | • | Holding power of strip up to | 3 Kg |
|---|------------------|------------------|---|------------------------------|------|
| • | Total thickness  | 650 μm           |   |                              |      |

For latest information on this product please visit http://l.tesa.com/?cp=NaN



# tesa® Waterproof XL

**Product Information** 

### **Properties/Performance Values**

| •<br>•<br>• | Ageing resistance (UV)<br>Application temperature from<br>Applicationfield<br>Area of use<br>Batteries included<br>Batteries required<br>Chemical Resistance<br>Hazard material<br>Humidity resistance | yes<br>15 °C<br>Bathroom, Kitchen<br>Indoor<br>no<br>no<br>no<br>yes<br>yes |
|-------------|--|---|
| •           | Humidity resistance<br>Oil and grease resistance   | yes<br>no   |
|             |  |   |

| <ul> <li>Ozone resistance</li> <li>Residue-free removability</li> <li>Solvent free</li> <li>Suitable surfaces</li> </ul>                                 | no<br>yes<br>yes<br>Marble, Glass, Metal,<br>Even wood, Most<br>plastics |
|--|--|
| <ul> <li>Temperature resistance max.</li> <li>Temperature resistance min.</li> <li>UV resistant</li> <li>Water resistance</li> <li>Waterproof</li> </ul> | 35 °C<br>15 °C<br>no<br>yes<br>yes                                       |

#### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

